

# WA2600-726-PTE AX1800 Outdoor Pole Mount Wi-Fi6 AP

## Datasheet

### Overview

The new generation series 802.11ax wireless access point WA2600-726-PTE independently developed by Maipu is an outdoor wireless access device (AP) that supports the latest 802.11ax technical standard. The product complies with the IEEE 802.11a/b/g/n/ac/ax standard, adopts a hardware-independent dual-frequency design, four spatial streams, and the whole machine can provide up to 1.8 Gbps access rate.

WA2600-726-PTE adopts a built-in antenna design that is simple and elegant with convenient deployment. It is outdoor pole mounted design for outdoor wireless coverage. It is suitable for large outdoor wide area coverage in financial park square, outside office building, smart city, etc. It comprehensively meets the deployment requirements of customers' outdoor scenes.



WA2600-726-PTE

### Highlight Features

- 802.11ax MU-MIMO Technology Supported
- Central Managed by WNC6600 Series Access Controller
- Seamless Layer2/3 Roaming Supported
- Self-Provisioning Networking Supported
- Rich Security Features for Wireless Network
- 1\*1000M Combo Ports + 1\*1000M PoE Out Interface
- Outdoor Pole Mounted Installation Design

# Key Features

## ● Gigabit optical port multiplexing

The WA2600-726-PTE outdoor AP provides up to two gigabit Ethernet ports and one gigabit SFP port for multiplexing, which can adapt to different customer's wired network link forms on site. It supports the SFP optical port to undertake data transmission. The Ethernet uplink port is used for the power taking of the PoE adapter. The networking is more flexible and convenient.

## ● High Performance Wi-Fi6 Access Point

The device supports dual-band concurrent 2.4GHz and 5GHz, and also supports Wi-Fi6 (802.11ax) standard protocol. It adopts 1024QAM modulation mode. The 5GHz band supports 2 spatial streams with a maximum negotiated rate of 1.2Gbps. The 2.4GHz band supports 2 spatial streams with a maximum negotiated rate of 0.6Gbps. The total wireless access rate of the device can reach 1.8Gbps.

It also integrates MU-MIMO and OFDMA technologies to subdivide the wireless channel into more sub channels, enabling simultaneous communication with multiple terminal devices. When multiple users access the internet at the same time, the user experience is significantly improved. It supports BSS Color spatial reuse function to color and use different mechanisms to process the basic service set, reducing interference, improving channel utilization, and achieving effects such as intelligent load balancing and 5G priority. It improves the 5G band utilization and increases the total number of devices.

## ● Comprehensive Security Protection

Together with the Maipu independently developed wireless controller, WA2600-726-PTE supports 802.1x authentication, MAC authentication, WEB authentication and other authentication methods to ensure network security.

It supports Multiple SSID technology, WA2600-726-PTE supports up to 16\*SSIDs, the administrator can set different passwords for each SSID, divide separate VLAN IDs, and easily achieve the effect of transmitting different services on different wireless networks (SSIDs). It can implement user isolation based on VLAN to ensure the security of data services in each VLAN.

It supports Wireless Intrusion Detection/Prevention (WIDS/WIPS), supports blacklists, whitelists and other wireless user access control features to detect, identify and counteract illegal wireless devices for effective blocking. At the same time, it also supports protection against ARP, SYN, port scanning and other network attacks to comprehensively build a secure and reliable network for users.

## ● Convenient Deployment and Intelligent Management

WA2600-726-PTE provides a portable design with a single arm handle and installation to ensure that the construction personnel always have one hand holding the ladder during ladder construction, avoiding device falling or even personal injury in operations with high risks such as arm clips and hugging.

WA2600-726-PTE can be automatically discovered by Maipu WNC6600 Series Wireless Controller and automatically download the configuration. The device automatically goes online with zero parameter configuration. It can be installed where wireless signal coverage is required to achieve truly flexible deployment, on-demand purchase and plug-and-play.

It can be managed by Maipu Matrix Center SNMP management system, this is a wired and wireless management platform for configuration management, topology management, fault management, performance monitoring, and upgrade management to greatly improve network operation efficiency.

## ● Environmentally Friendly Design and Energy Saving

WA2600-726-PTE integrates energy-saving technologies such as target wake-up time technology, MIMO power saving technology, and packet power control technology. By reducing the number of terminal wakeups, improving antenna efficiency, and integrating highly efficient power supply designs, it achieves energy saving and power saving.

# Technical Specifications

Product Model	WA2600-726-PTE
Version	M1
<b>Interface Specification</b>	
Service Port	1*10/100/1000M Base-T adaptive Ethernet Combo Port, 802.3at PoE (LAN1) 1*1000M Base-X SFP Fiber Combo Port 1*10/100/1000M Base-T adaptive Ethernet Port, 6.5W PoE Out (LAN2)
Indicators	1*Multi-Color LED (For System and Radio status)
Other Port	1*Reset Button (Factory reset; WPS) 1*RJ45 Console Port
<b>Environment Specification</b>	
Working Temperature	-40°C to +65°C
Working Humidity	0% to 100% non-condensing
Storage Temperature	-50°C to +85°C
Storage Humidity	0% to 100% non-condensing
IP Rating	IP68
Weight	1.9 kg
Dimension (W*D*H) mm	275mm*230mm*80mm
<b>Hardware Specification</b>	
Installation Mode	Pole Mounting
Power Supply	PoE: IEEE 802.3af/802.3at-compliant (compatible).
Power Consumption	<25W
<b>Radio Specification</b>	
RF Design	Dual-radio design, one 2.4 GHz radio and one 5 GHz radio - Radio1: 2.4 GHz, 2 streams: 2*2 - Radio2: 5 GHz, 2 streams: 2*2
Operating Bands (Country-specific restrictions apply)	- Radio1: 2.400 to 2.4835GHz - Radio2: 5.150–5.350GHz, 5.47–5.725GHz, 5.725–5.850GHz
Transmission Rate	- 802.11b: 1Mbps, 2Mbps, 5.5Mbps, 11Mbps - 802.11a/g: 6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps - 802.11n: 6.5Mbps-300Mbps (MCS0-MCS31, HT20-HT40), 400Mbps with 256-QAM - 802.11ac: 6.5Mbps-866Mbps (MCS0-MCS9, NSS=1-2, VHT20-VHT80) - 802.11ax (2.4GHz): 8.6Mbps-574Mbps (MCS0-MCS11, NSS=1-2, HE20-HE40) - 802.11ax (5GHz): 8.6Mbps-1,202Mbps (MCS0-MCS11, NSS = 1-2, HE20-HE80)
Antenna	Built-in High Gain Smart Antenna Matrix
Antenna Gain	2.4 GHz: 10 dBi 5 GHz: 10 dBi Directional Antenna
Maximum Transmit Power	2.4 GHz: +27 dBm 5 GHz: +27 dBm The actual transmit power complies with the regulatory requirements for radio frequency emissions in various countries and regions
Transmit Power Adjustment	1 dBm
Modulation Mode	- 802.11b: BPSK, QPSK, CCK - 802.11a/g/n: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM

	<ul style="list-style-type: none"> <li>- 802.11ac: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM, 1024-QAM</li> <li>- 802.11ax: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM, 1024-QAM</li> </ul>
Modulation and Encoding	<ul style="list-style-type: none"> <li>- Low Density Parity Check (LDPC)</li> <li>- Maximum Likelihood Detection (MLD)</li> <li>- Beamforming</li> </ul>
Advanced RF Features	<ul style="list-style-type: none"> <li>- Channel Rate Adjustment, include TPC (Transmit Power Control)</li> <li>- ACS (Automatic Channel Scanning)</li> </ul>
<b>WIFI Specification</b>	
WIFI Standards	- IEEE 802/11a/b/g/n/ac/ax
SSID Numbers	8*SSIDs
Channelization	20, 40, 80 MHz
Recommend Users	64-128
Working Mode	Fit Mode
Security Type	Open, PSK, WPA-Personal, WPA-Enterprise, WPA2-Personal, WPA2-Enterprise, WPA3-Personal, WPA3-Enterprise, Portal, 802.1X, Radius
Working Bandwidth	<ul style="list-style-type: none"> <li>- 802.11ax: HE80, HE40, HE20</li> <li>- 802.11ac: VHT80, VHT40, VHT20</li> <li>- 802.11n: HT40, HT20</li> </ul>
Date Rate	<ul style="list-style-type: none"> <li>- Radio1: 2.4 GHz, 574 Mbps</li> <li>- Radio2: 5 GHz, 1201Mbps</li> <li>- Combined: 1.8 Gbps</li> </ul>
MIMO Technologies	<ul style="list-style-type: none"> <li>- Multi-User Multiple Input Multiple Output (MU-MIMO)</li> <li>- Maximum Ratio Combining (MRC)</li> <li>- Space-Time Block Coding (STBC)</li> <li>- Cyclic Delay/Cyclic Shift Diversity (CDD/CSD)</li> <li>- Dynamic MIMO power saving</li> </ul>
Energy Saving	<ul style="list-style-type: none"> <li>- U-APSD</li> <li>- SM Power Save</li> <li>- Green AP mode</li> </ul>
Advanced WIFI Features	<ul style="list-style-type: none"> <li>- Orthogonal Frequency Division Multiple Access (OFDMA)</li> <li>- Short GI (Short Guard Interval)</li> <li>- DFS (Dynamic Frequency Selection)</li> <li>- Spectrum Navigation</li> </ul>

# Order Information

Model	Description
WA2600 Series Wi-Fi6 Access Point	
WA2600-726-PTE	M1 Version: WA2600-726-PTE, Outdoor pole mount Wi-Fi6 802.11a/b/g/n/ac/ax, Dual frequency, dual mode, forwarding performance of the whole device 1.8Gbps, 2:2 MIMO, PoE power input, inbuilt directional antennas, IP68, 1*1000M Combo Port (PoE), 1*1000M LAN Port. (installation accessory included)

# Application Scenario



All rights reserved. Printed in the People's Republic of China.

No part of this document may be reproduced, transmitted, transcribed, stored in a retrieval system, or translated into any language or computer language, in any form or by any means, electronic, mechanical, magnetic, optical, chemical, manual or otherwise without the prior written consent of Maipu Communication Technology Co., Ltd.

Maipu makes no representations or warranties with respect to this document contents and specifically disclaims any implied warranties of merchantability or fitness for any specific purpose. Further, Maipu reserves the right to revise this document and to make changes from time to time in its content without being obligated to notify any person of such revisions or changes.

Maipu values and appreciates comments you may have concerning our products or this document. Please address comments to:

*Maipu Communication Technology Co., Ltd*  
No.16, Jiuxing avenue  
Hi-Tech Zone  
Chengdu, Sichuan Province  
P. R. China  
610041  
Tel: (86) 28-65544850,  
**Fax:** (86) 28-65544948,  
**URL:** [http:// www.maipu.com](http://www.maipu.com)  
**Email:** [overseas@maipu.com](mailto:overseas@maipu.com)

All other products or services mentioned herein may be registered trademarks, trademarks, or service marks of their respective manufacturers, companies, or organizations.